

Outside size:(mm)	<u>7000x5560x3430</u> LxWxH	Inside size:(mm)	<u>6900x4000x2700</u> LxWxH	
Front door:(mm)	3000x2700 WxH	Total power: (kw)	<u>17</u>	
Cabin system	Wallboard	EPS (epispastics polystyrene) Colorful Steel Skin Boards, 50mm Thick, Tongue & Groove Style, Compound Construction, Aluminum-alloy Frame. Anti-flame and Heat-Insulation, Galvanized steel roof panel		
	Basement	Galvanized Steel Sheet and Square steel pipe assembling, Grid &embossed plate floor, Two embossed steel ramps		
Air circulation system	Inlet fan	Model: YDW	Outlet fan	Model: YDW
		Blower capacity: 25000m³/h		Blower capacity: 25000m³/h
		Pressure 815Pa		Pressure 815Pa
		Rolling speed: 900rpm		Rolling speed: 900rpm
		Power: 7.5kw		Power 7.5kw
		Quantity: 1 sets		Quantity1set
	Air volume: <u>25000 m³/h</u> ; Air speed: <u>0.35m/s</u> ; Air recycling time: <u>280 times/h</u> ;			
Air purification system	Dual filtering structure. The primary filter can capture granules larger than 10µm. Ceiling filter captures granules bigger than 4µm. Its filter rate reaches 98%. TSP ≤1.4mg/m³			
Heating System	Burner	Italy Riello Brand, G20 Diesel Burner, 180000Kcal/h, 10N Damp Motor		
	Heat exchanger	SUS304 Stainless Steel heat exchanger, argon arc welding;		
	Max temp:80 ℃; Heating time:5-7 mins (20-60 ℃); Fuel consumption: 4-6kg/vehicle;			
Light system	Ceiling light: 32pcs 36w Philips lamp, Bottom Light: 16 pcs 36w Philips Lamp, 1000 Lux, With tempered glass and hot line			
Electric controlling system	Micro-computer programmed controlling, Spray & Baking Switch, Light Switch, Emergency Stop, Breakdown Alarm, Failure alarm, timer			
Environmental system	Multi-layer fiberglass filter, active-carbon			
FOB GZ PRICE	USD9785/SET			