

XYX-3 model Trailer mounted drilling rig



Specification

Drilling depth	m	100	250	300	600
Drilling DI	mm	300	200	150	75
Open hole DI	mm	300			
End hole DI	mm	75			
Drilling rod	mm	Φ60			
Drilling angle		90°-65°			
Rotary Spindle					
Spindle forward speed		r/min		30-1050	
Spindle reverse speed		r/min		29-137	

Spindle stroke	mm	560
Spindle inner diameter	mm	96
Spindle lifting capacity	KN	60
Main Winch (drive hydraulic system)		
Single line lifting speed	m/min	0-45
Hug floodgate belt width	mm	90
Tightrope diameter	mm	14
Hoist single line lifting capacity	KN	40
Roller diameter	mm	200
Roller cubic measure	m	30
Mud pump		
Horizontal Triplex BW-200 mud pump		
Displacement	L/min	200
Work pressure	Mpa	4-6
Water inlet caliber	mm	65
Water to exit caliber	mm	37
Gear Oil pump		
Duplex gear oil pump CBF-F63/25		
Front displacement、 pressure		63mL/r 20Mpa
Behind displacement、 pressure		25mL/r 20Mpa
Drilling rig Power		
Diesel engine	Hp	4100# 46HP
Electric motor	KW	Y180L-4 22KW

ADD: Economic development zone Mengyin county Linyi city shandong,P.R,China

Http:// www.chinajulong.cc

E-mail: julongmachine@163.com