



A2FM80/61W-VZB Motor adapter

Technique Parameter	
rated input torque	T1nom 195 N.m
max input torque	T1max 304 N.m
rated input speed	n1nom r/min
max input speed	n1max 3000 r/min
ratio	i 82.4
rated output torque	T2nom N.m
max output torque	T2max 16000 N.m
rated output speed	n2nom 25000 r/min
max output speed	n2max 37 r/min
motor max pressure	Pmax MPa
motor work max. pressure	P MPa
brake type	disk brake normally open
static brake torque	TBr 0-4000 N.m
brake port oil pressure	P 0-40 Bar
brake port max. oil pressure	Pmax. 40 Bar
driving device	A2FM80/61W-VZB
lubrication brand	ISO VG 220
oil volume	L

CUSTOMER	CUSTOMER P./N.		
REV	AUTH	DATE	MAKE
THE REPRODUCTION, DISTRIBUTION AND UTILIZATION OF THIS DOCUMENT AS WELL AS THE COMMUNICATION OF ITS CONTENTS TO OTHERS WITHOUT THE EXPRESS AUTHORIZATION IS PROHIBITED. THE PAYMENT OF FINANCES AND RIGHTS IS RESERVED IN THE EVENT OF THE GRANT OF A PATENT, UTILITY MODEL, OR DESIGN. (PER ISO 15015)			
CART CODE	ITEM	PART NO	PART NAME
DOC NO	DATE	DATE	DATE
DRFTER	DESIGNER	ENGINEER	RAW PART NO
TITLE NB709S3-82-A2F80Z -M12Z18XOB120 SLEWING GEARBOX		MATERIAL / SPECIFICATION SIZE A4	
Dwg NO 258B		REV 01	