



北京九虹中工工程机械有限公司
 Beijing Jiuhong Heavy Industry Machinery Co., Ltd
 Xisha Industrial Park, Beiqijia Town, Changping District, Beijing, China

TO				DATE	
website	www.bjfh.com				
TEL	86-10-81760978	FAX	86-10-81769546	EMAIL	business@bjfh.com

Technical specification of ZLP

Name		Technical parameter		
Model		ZLP800	ZLP630	
Rated load		800Kg	630Kg	
Lifting speed		8-10m/min	8-10m/min	
Platform Dimension L×W×H(mm) Spray plastics corrosion-resistant		7500(2.5m*3)×720×1300	6000(1+2+3m)×720×1300	
Lifting Height		100 m	100 m	
Cable		100 m	100 m	
Steel rope (specially-made)		Φ9.1mm	Φ8.3mm	
Hoist	Pulling power		7.84KN	6.17KN
	electric motor	model	YEJ100L-4	YEJ90L-4
		Power	1.8KW*2	1.5KW*2
		Voltage	380V/220 3phase	380V/220v 3phase
		Rotational speed	1420rpm	1420rpm
	Braking moment	15Nm	15Nm	
Safety lock	Permission force of impact		30KN	30KN
	Locking Cable Angle		3°~8°	3°~8°
Suspension mechanism (galvanized)	Front beam overhang		1.3~1.5m	1.3~1.5m
	Support adjustable height		1.44~2.14m	1.44~2.14m
Counterweight		1000kg	800kg	
20'ft container		8sets	9sets	
FOB Tianjin	A-alloy platform		USD 2810	USD 2610
	Hot Dipping Platform		USD 2590	USD 2420
	Steel platform		USD 2520	USD 2350
Note: 1.The quotation efficient duration: 1 month 2.Payment term:T/T Delivery time:7-15days 3. The Voltage and Frequency could up to different countries' standard. 4.Counterweight is made of cement(25KG/piece)				