

Performance and Features of SCM8021 Grinding Mill

1.High Efficiency

Under the same final size and power, the product capacity of ultrafine mill is twice than jet mill and agitation mill.

2.Longer Lifetime of Spare Parts

The roller and ring are made of special material, which improve the grinding efficiency a lot. For same material and final size, the lifetime of its wearing parts can reach to more than one year, about 2-5 times as long as that of vertical shaft impact crusher and turbo-mill. Especially when

handling calcium carbonate and calcite the lifetime can reach 2-5 years

nanuning calcium caroonaic and calciu, inc menine can reach 2-5 years.

3. High Safety and Reliability:

There are no rolling bearings and bolts in grinding cavity, so problems caused by bolts shedding or wear of bearings and seal components will never happen.

4.High Fineness of Products

The product fineness can reach D97≤5µm.

5. Environment Friendly

The application of pulse dust collector and muffler reduce the pollution and noise of the dust, which has reached national environment protection standard.

Quotation for the SCM8021 Powder Grinding Line						
No	Item	Model	Power(K W)	Q'ty (set)	Unit Price (USD)	Price (USD)
1	Bucket Elevator	TH200,8.13M	4	1	2800	2800
2	screw conveyor	LS219*6.5M	5.5	1	1990	1990
3	Storage hopper	1.5m*1.5m		1	750	750
4	classfier	HGM80	18.5	1	5900	5900
5	doublecyclone powder collector	CLK500*2		1	3700	3700
6	bag filter	DMC120		1	8500	8500
7	blower &muffler	9-26-6.4A	45	1	2900	2900
8	wind -pfoff dischargeing valve	ZJD200, 6L	1.5	2	600	1200
9	vibrating feeder	GZ1F	0.06	1	580	580
10	compulsor screw conveyor	219-4.5M	3	1	900	900
11	sound-proff cabniet	2.76*2.4*2.35		1	1680	1680
12	HGM80 grinder mill	HGM80	75	1	30500	30500
13	Air compressor	KSH100D	7.5	1	1800	1800
14	automatic electric control system(siemens)	HGM80	170	1	3500	3500
15	Total Final Price	FOB Shanghai			\$66,700	
REMARK: The price include the main unit and the motor.						
Materials of SCM8021 Mill Main Component Equipment						
No	Item	Materials		Picture		
1	Grinding Roller	Manganese Alloy		3		

2	Grinding Ring	Manganese Alloy			
3	Shaft Pin	Steel 45			
4	Classifier Impeller	Wear-resistant Alloy			
5	Turnplate	Wear-resistant Alloy			
6	Diaphragm	Wear-resistant Alloy			
	Details of SC	M8021 Mill Comp	onent Equi	pment	
	Item		Ring Micro Grinding Mill		
Model			SCM8021		
Main Shaft Speed (r.p.min)			240		
Roller Numbers(pcs)			21		
Ring Diameter (mm)			Φ800		
Ring Numbers(pcs)			3		
Max Feeding Size(mm)			≤ 20		
Output Size(um)			5-47		
Capacity(t/h)			0.6-2t/h		
Motor Power(kw)			55 13900×4000×6200		
Overall Dimension(m)			13900×4000×0200		

Picture			
Item	Bucket Elevator		
Capacity (m ³ /h)	17.87		
Distance between bucket /mm	500		
Volume of bucket /L	1.5		
Chain Number/Pcs	9		
Drive sprocket rotation speed (r/m)	36		
Conveying material size /mm	0-30		
Power/kw	3		
Height/m	8.13		
Picture			
Item	Double Cyclone Powder Collector		
Working principle	Theory of gravity		
Collecting rate	80%		
Item	Blower and Muffler		
Wind capacity /m ³	12810		
Wind pressure /Pa	11430		
Motor Power(kw)	45		
Item	Bag Filter		
Filter bag number /Pcs	120		
Bags Size	96		
Dust collector efficiency	99%-99.5%		
Pulse valve number	15		

Dimension /m	5.2*2.3*5.7		
Picture			
Item	Feeding silo		
Volume /m ³	3.5		
Diameter /mm	1500		
Item	Compulsory Screw Conveyor		
Tube diameter /mm	159		
Rotate speed (r/min)	8.3		
Conveying capacity (m ³ /h)	2_7		
Picture			
Item	Air compressor		
Pressure /Mpa	1		
Capacity (m ³ /min)	1.05		
Power /kw	11		
Dimension /mm	1650×600×1200		
Item	Electrical controlling system		
Control model Electron component	PLC CHANT &SIEMENS		
Dimension /mm	1200×660×2000		
Picture			
Item	Sound-proof Cabinet		
Quan as Thisley	100mm		
Sponge Thickness	10011111		

Terms and Conditions

1. Delivery: 30 days after receipt of deposit.

2. Price terms: FOB Shanghai Price .

3. Packing: 1 set of 40GP .The products should be processed to be rustproof and moisture proof before delivery. The small parts are packed into wooden crates; the big parts are wrapped by plastic sheeting.

4. Payment: T/T. Deposit (30% of total amount) to be paid after signing the sales contract, the rest amount to be paid after inspection and before goods leaves factory.

5.Opening Bank: HUINAN SUB-BRANCH BANK OF CHINA SHANGHAI Bank address: HUINAN TOWN, NANHUI DISTRICT, SHANGHAI, CHINA USD Account No: 0494 8443 6459 2627 80 SWIFT CODE: BKCH CN BJ 300

6. Installation: If required, we will send the engineer to guide your workers to install the machine, take trial run; the buyer should prepare the materials and tools needed, and offer necessary assistance. The actual expenses incurred for accommodation, to and fro travel for the engineer, and insurance, should be borne by the buyer. The buyer should pay one engineer 60USD for first month and 80USD for each additional day.

7. Warranty: 100% brand new when leaving the factory. The seller guarantee quality of the machines (excluding wearing parts) for a period of two years from the date of trial run finish under our technician's guidance, but not exceed 27 months from date on which machine leaves the factory.

8. Valid time: This quotation will be effective within 20days after issuing.

9. Issuing Date: May 8 th,2015

SCM100L in workshop and Certifiacte CE ISO









