## 钰 YUXIANG

## 广州市钰翔轻工机械设备有限公司 Guangzhou Yuxiang Light Industry Machinery Equipment Co.Ltd.

Company Add: 1st Floor, Building A ,No.20, Hetai Road, Hebian, Jiahe, baiyun District, Guangzhou.Factory Add: Shanguang New Industrial Zone, Cheluo Town, Gaoyou, Jiangsu Province.Email ID: yx006@chinayxjx.comWhatsapp/Wechat ID: 13710320716MP: 0086-13710320716Attn: Riphen zhang

## Main Product



# Main Product-- (specialized in produce cosmetic & chemical machinery):

Cream & Lotion production line	Lipstick production line	
Shampoo production line	● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●	Eye shadow production line
Perfume production line	Toothpaste production line	

Quality first, credibility oriented, management oriented, sincere service.

<mark>广州市钰翔轻工机械设备有限公</mark> Guangzhou Yuxiang Light Industry Machinery Equipment Co.I

## **\* Machine's Quotation:**

No.	Description	Picture	Qty.	Unit Price (USD/SET)	Total Price (USD)
1	RHJ-C-50L Vacuum Emulsifying Mixer				
	<ul> <li>making cream,lotion, paste,etc.</li> <li>homogenizer on the top, two-way stirring up mixer; with oil and water tanks;</li> <li>electric heating,water cooling;</li> <li>Siemens motors,Taiwan Delta inverter,French Schneider buttons;</li> </ul>		1 set	13800	13800
	TOTAL VALUE : USD FOB Guangzhou				

#### SAY US DOLLARS FOURTEEN THOUSAND ONEHUNDRED AND SEVENTY ONLY

## **\* Machine's Specification:**

## Yuxiang RHJ-C-50L Vacuum Emulsifying Mixer

#### Feature:

This unit adopts top coaxial triplet blender, hydraulic raise-fall open cover, rotate speed of low-speed wall-scrapping blender is: 0-80r/min (frequency conversion timing), homogenizer adopts high Shearing eddy emulsifying blender, low-speed wall-scrapping blender stick to boiler bottom and boiler wall automatically. It adopts vacuum suction and especially adopts vacuum suction to powder material to avoid powder flying everywhere. This unit accords with GMP manufacture requirement completely and is most advanced and ideal cream and frost production equipment in China.

Quality first, credibility oriented, management oriented, sincere service.





## 广州市钰翔轻工机械设备有限公司 Guangzhou Yuxiang Light Industry Machinery Equipment Co.Ltd.



## Technical Parameter:

1.Main pot (3 layers)				
No	Item	Description	Remark	
1.1	Volume	Full volume: 60L, capacity: 50L	Loading coefficient 0.8	
1.2	Heating	Electric heating, power: 3KW	Normal pressure	
1.3	Structure	3 layers, hydraulic lift system, tilt discharge products, clockwise &counter-clockwise mixing way, top homogenizer		
	The second	Image: Weight of the second		
1.4 Material Internal layer: SUS316L, thick: 5mm		Stainless steel from: Finland		

Quality first, credibility oriented, management oriented, sincere service.

钮 YUXI	<sup>E</sup> ジェス Suangzhou Yuxiang Light Industry Machinery Equipment Co.Ltd.				
			Middle layer: SUS304, thick: 5mm	Quality certificate	
			External layer:SUS304, thick 3 mm	Insulation media: aluminum silicate	
			All material touch part is SS316, include homogenizer and disperser, valve, etc.		
			Material filter, vacuum pressure meter, vacuum		
]	1.5	Lid	discharge valve, vacuum inlet, positive pressure inlet, CIP spray ball, sight glass light, sight window, man-hole, hopper	Sanitation grade accessories & valves	
	1.6 Mixing parameter		Clockwise & counter-clockwise mixing	SUS316L	
]			Power: 1.1KW, speed: $0 - 80$ rpm	Siemens motor Taiwan Delta	
Siemens motor       Taiwan Delta inverter       Sight window & high temperature resistance quartz glass       spray ball				spray ball	
		Homogenizer	Top homogenizer	SUS316L	
1	1.7	Homogenizer technical parameter	Power: 2.2KW, speed: 0 – 3000 rpm	Siemens motor; Taiwan inverter	
		Processing methods	Rotor and stator adopts wire-cutting finish machining, polishing treatment before assembly	Axis adopt dynamic balance processing	
]	1.8	Sealing	Adopting Germany Bergman mechanical seal, NSK bearing made in Japan	<u>S</u>	
1	1.9	Polishing level	Internal and external sanitation polishing, fully meet the requirements of GMP hygiene standards;	320U	
2	2.0	Water-ring Vacuum     0.75KW		Siemens Brand	

Quality first, credibility oriented, management oriented, sincere service.

# 「小竹市钰翔轻工机械设备有限公司 Guangzhou Yuxiang Light Industry Machinery Equipment Co.Ltd.





NSK bearing made Adopting Germany Bergman			nan	
	in Japan	mechanical seal		
2. Water pot technical parameter (3 layers):				
No	Item	Configuration and technical parameter	Note	
2.1	volume	Full volume: 48L, capacity:40L;	Loading coefficient 0.8	
2.2	heating	Electric heating, power: 6KW;	Normal pressure	
2.3	structure	Three layer, on the cover, coping with unilateral quickly dispersion, the material out from bottom;		
		Internal layer: SUS316L, thick: 4mm	Stainless steel from:Finland	
2.4	Material	Middle layer: SUS304, thick:4mm	Clip set of thickness: 50mm	
	<b>ET</b>	External layer:SUS304, thick 3 mm	Insulation medium: guisuanlu:	
2.5	Dispersion.parameters	Top inclined insert installation, scattered motor power for 0.37 KW, scattered speed for 960 R.P.M	Siemens motor	
2.6	Polishing level	Internal and external sanitation polishing, fully meet the requirements of GMP hygiene standards	320U	
3. Oil po	ot technical parameter (3 la	iyers):		
No.	Item	Configuration and Technique Parameters	Note	
3.1	Design Capacity	Full volume: 30L; Working volume: 25L;	loading coefficient0.8	
3.2	Heating Method	The jacket is electrical heating 6KW	operating pressure is normal pressure	
3.3	Basic structure	Three layers, opening on the side, top with fast scattered, bottom discharging;		
		Contact parts material: SUS316L; thickness: 4mm;	Imported material: Finland	
3.4	tank material	The jacket is electrical heating: SUS304, Thickness: 4mm	Include material certificate	
		Outer insulating layer: SUS304, Thickness: 3mm	Insulation medium: pure aluminum silicate	

Quality first, credibility oriented, management oriented, sincere service.

「小市钰翔轻工机械设备有限公司 Guangzhou Yuxiang Light Industry Machinery Equipment Co.Ltd.				
3.5	Dispersion parameter	The top installs inclined insert. Distributed motor power: 0.37KW. Disperse rotate speed: 960r/min;	Siemens motor	
3.6	Polishing grade	Polished inside and outside are sanitary degree, completely fit GMP hygienic standard	320U	
	high speed dispersion	plate Siemens motor		
4. Elect NO.	ric control system:	Configuration and technical parameter	Note	
	Electric control connect with Main frame	outer layer material: adopt SUS304 Stainless steel plate, thickness:2mm	Stainless steel plate	
4.1		Meter: thermometer, Time digital display met, Current voltmeter	Delixi brand	
4.1		Button: Each function switch control button, Power indicator light, scram etc.	Schneider	
<u>/</u>	The electrical components: include various control relay	Delix		
			A State	
Schneider	r Electric button Digital	display type time relay Temperature control meter	voltmeter	
Schneider 4.2	r Electric button Digital lifting system	display type time relay Temperature control meter Hydraulic elevator way, oil pump power:0.55KW;	voltmeter include hydraulic oil	

\* Some photos with my customer:

we Provide machine not only for domestic customer, but also have customers from Turkey, Brazil, Spain, Slovenia, German, France, Korea, Indonesia, Malaysia, India, Vietnam, Saudia Arabia, Dubai, Ethiopia, Algeria, Nigeria, Uganda, Egypt, Dubai, USA, Austria, and so on, and we get good feedback from them.

Quality first, credibility oriented, management oriented, sincere service.



**※ Factory picture:** 



Quality first, credibility oriented, management oriented, sincere service.





## **※ Exhibition shop picture:**



**\* Company Certificate:** 

#### **Business license of head-company and factory**



Quality first, credibility oriented, management oriented, sincere service.

Guangzhou Yuxiang Light Industry Machinery Equipment Certificate of Foreign Trade Dealers, SGS, CE, CCIC SGS Ade-in-China.com CERTIFICATE OF CONFORMITY 对外贸易经营者备案登记表  $(\mathbf{C})$ 141 建出口3 "州市县期轻工机械设备有限公司 YUXIANG LIGHT Audit Date 04 Aug. 2011 CERTIFICATE OF QUALITY MANAGEMENT SYSTEM A, SHISHENG INDUSTRIAL ITION CENTER , GUANG HUA 40 SECTION), BAIYUN Rogy Co., LM. (Made in China

YANGZHOU YUXIANG LIGHT INDUSTRY MACHINERY EQUIPMENT FACTORY

ng quality management s ISO9001: 2000 CERTIFICATION SCOPE: LIGHT INDUSTRY MACHINERY EQUIPMENT

3283A CANADO

### **X** Sales-service information:

ARBICHA

China Guangdong Guangzhou Bayu

印香认真词读背面的条款 并自企业法定代表人或个体工商会资人签字

4.14

Price Basis: EXW Guangzhou, we can responsible for send the goods to your ware house which in Guangzhou city (also can accept offer the FOB, CFR, CIF price)

CE

----

**Delivery Time:** Within 35 working days since the receipt of 30% deposit.

SOS-MIC 06666

Guangahou Yuxiang Light Indu

Sign for and or

Payment Term: 30% deposit by T/T before production, 70% balance should be paid by T/T before shipment. 

Package: Plywood Case Packing

Warranty: One year since the date of installation. If there is any wearing part be broken within the warranty and isn't caused by un-properly operation, then the Seller would offer the new parts for free. **Inspection:** The buyer will do the machine inspection when the machines are ready.

Machine Installation or Fixing: If Buyer requires Seller's engineer to install or fix the machine locally in due course, the Buyer should pay the round air ticket cost and arrange the hotel accommodation as well as the means for Seller's engineer.

The validity time of this quotation is 30 days. If the current exchange rates on order date lower than guotation date, we suggest you pay the amount as according to the current exchange rates on order date. (Now offer date's exchange rate USD: RMB=1: 63)

9

Quality first, credibility oriented, management oriented, sincere service.