## JINYI PURIFICATION TECHNOLOGY LTD

Add: Building 2, No. 18, Jingfu Road, Xiabian Village, Chang'an Town, Dongguan City Tel: 86-769-23120086 Fax: 86-769-23120096







## **PRODUCTS CATALOG**


### Clean room design, manufacturing, construction

Jinyi Purification Technology Ltd provides one-stop service in clean room such as hospital operating room, industrial workshop and so on. We can provide clean room wall panel, ceiling panel, air circulation system, air shower, pass box, Hepa filter, FFU, HEPA BOX, air diffuser, LED light etc for equipment.









Wall/ceiling panel	Machine-made or Hand-made sandwich board
Clean room equipment	Air shower, FFU, Pass box, Laminar flow cabinet, HEPA box
Cleanliness	Class100-100000
Purification system	HVAC, or AC conditioner + FFU
Floor	PVC anti-static floor or epoxy-based coating
Other accessories	Stalinite window, LED panel light, Door, Hand wash sink, storage/shoe cabinet ETC
Service	Design, manufacturing, construction

## Clean room wall and ceiling board type

Sandwich panel	Double steel +Sulfur oxygen magnesium filler	Double steel+ rock wool filler	Double steel+ PU filler	Double steel + MGO filler	Double steel + EPS filler
Fire proofing	A	A	A	A	В
Weight Capacity	180kg/m2	80kg/m2	100kg/m2	100-150kg/m2	80kg/m2
Size	1150/1180mm width, height customized	1150/1180mm width, height customized	1150mm, height customized	1150/1180mm width, height customized	1150mm, height customized
Steel thickness	0.376mm, 0.426mm, 0.476mm, 0.526mm, 0.576mm				
Thickness	50mm, 75mm, 100mm				
Installation	<ol> <li>we send engineer to customer side</li> <li>construct out to construction team</li> <li>customer send technicist to our company for free studying</li> </ol>				



## Clean room accessories we can supply

#### **CLEAN ROOM DOOR**

Form a complete set for all levels of clean room, purification room, dust-free room, trailer and other places using color plate partition. Around double sealing, thermal insulation, heat insulation, sound insulation. Color plate or stainless steel plate can be used to customize different size of clean door, locks, color of color steel, door strip, ETC ,can be configured in accordance with the requirements.





Product Name	Clean Room Door		
Material	Stainless Steel 304/316(L) or polyurethane sandwich panel		
Size	Single Door W:700mm*H:2100*T:50 mm W:800mm*H:2100*T:50 mm W:900mm*H:2100*T:50 mm	Double Door W:1200mm*H:2100*T:50 mm W:1500mm*H:2100*T:50 mm W:1800mm*H:2100*T:50 mm	
Observation Window	Available		
Window size	5mm thickness tempered glass 400mm*600mm/400mm*400mm,right or round corner		
Window Frames	Aluminum Profile		
Surface	Electrostatic Powder Coating Processing		
Color	Blue or customized		
Core	Paper honeycomb/Rock Wool/PU		
Open Method	Swing or automatic(optional)		
Seal	3m industrial tape seal, neutral silica gel		
Dry	Inner adding molecular sieve desiccant		



Automatic Rolling shutter door			
Using location	Internal & External door		
Door curtain material	Unique and professional 0.8-1.2mm fabric		
Door frame	Standard steel door frame		
Controlling system	PLC		
Door Designing	Unique for the larger size		
Moto location	Both side are ok		
Safety equipment	Standard light		
Wind load max	28m/s		
Opening speed	0.6-1.2m/s		
Closing speed	0.6m/s		
Closing opening speed	350-650mm/sec		
Door operation	High frequency motor		

#### **AIR SHOWER**

Air Shower is used to blow away dust on clothing, equipment, materials and tools before workers or objects enter the Clean Room; meanwhile, its Air Lock function may effectively control personnel passing in and out, as well as act as various levels of buffer room for clean room to prevent cross pollution.



## HEPA FAN FILTER UNIT(FFU)

FFU fan filter unit is type of unit used for filtering laminar air and supplying clean air. FFU can be used stand alone or installed modularly. FFU is the core when making clean room equipment for a given space including clean booth, clean bench and clean room assembly



#### 1175\*575\*260MM

Power consumption: 1100W Cleanliness of location air : Class100, Class1000,Etc Efficiency: 99.99%/99.995% H13 or H14 Material: Baking finished, SUS201, SUS304, Galvanized zinc coated steel Power supply: AC 220/50-60Hz

#### 575\*575\*260MM

Power consumption: 80W Cleanliness of location air : Class100, Class1000,Etc Efficiency: 99.99%/99.995% H13 or H14 Material: Baking finished, SUS201, SUS304, Galvanized zinc coated steel Power supply: AC 220/50-60Hz





#### **Stainless steel FFU**

Name: FAN FILTER UNIT Brand: JINYI Original: GUANGDONG, CHINA SUS304, SUS201 optional, H13 or H14 HEPA filter optional, aluminum fan, AC 220V\*50-60HZ

### PASS BOX

The Pass through box is a clean room auxiliary equipment, its function is to purify the goods pass the buffer between indoor and outdoor clean area to prevent items due to the pass to open the door and destroyed the clean room air and chamber pressure, more can reduce the operating personnel move to prevent the entry of the dust of the outer region, the stability of the clean room.





Туре	Static pass box	Air shower pass box	
External dimension(mm)	800*690*690(W*H*D)	800*1200*690(W*H*D)	
Internal dimension(mm)	600*600*600(W*H*D)	600*600*600 (W*H*D)	
External material	SUS304, SUS201, baking finished		
Internal material	SUS304 stainless steel		
Door Lock	Mechanically or electronically interlocked		
Noise	~	<65dBA	
Power supply	~	220v 50/60HZ, 280W	
Efficiency	~	99.99~99.995%	
Air filter	~	H13 or H14 optional	
Remark	Above is standard specs, the dimension can be customized as requested		

### **OTHER PARTS**

