

YUYAO NO. 4 INSTRUMENT FACTORY



No. 66 Changxin Rd, Yuyao City,
Zhejiang, China
Tel: +86 574 62833672
Fax: +86 574 62811735

PRODUCT INTRODUCTION DF/DFD-CF SERIES

specification

medium:	water, air, oil(below 20cst)
Medium temperature:	-5~80°C
Mode of Action :	Pilot operated
Working type	Normally closed/ Normally open
Body material:	Cast iron
Working pressure	0.3~8
Sealing material:	NBR
Coil protection index:	IP54 (DF-CF) / IP65 (DFD-CF)
Coil power	AC220/110V 50/60HZ; DC24V/12V, also available for other voltages DN25~100MM AC 18VA DC20W; DN125~200MM AC 20VA DC28W

parameters

model	connection	orifice size (mm)	CV value	L (mm)	H(mm)
DF/DFD-40CF	FLANGE	40	21	169	196
DF/DFD-50CF		50	30	200	200
DF/DFD-65CF		65	53	260	280
DF/DFD-80CF		80	82	280	287
DF/DFD-100CF		100	128	352	330
DF/DFD-125CF		125	222	430	437
DF/DFD-150CF		150	292	454	460
DF/DFD-200CF		200	513	573	547

Pictures



DF-80CF



DF-150CF